

Y.B.

L^AT_EX Class yb-book*

Yegor Bugayenko
yegor256@gmail.com

2026-07-16, 0.12.0

1 Introduction

The class yb-book was devised to assist the author in producing [his books](#) and in publishing them [on Amazon](#). Others are welcome to employ it for their own books. The procedure is straightforward:

```
\documentclass{yb-book}
\renewcommand*\thetitle{New Book About OOP}
\renewcommand*\theauthor{Jeff Lebowski}
\renewcommand*\thevolume{1}
\renewcommand*\theversion{1.0}
\begin{document}
\ybPrintTitlePage
\chapter{First One}
\section{About Something Interesting}
Hello, world!
\end{document}
```

Suggestions for additional options and commands are welcome; nevertheless, the style of the author's books is intentionally as plain as possible, eschewing formatting to the greatest extent practicable. The reasoning is set out [here](#).

2 Options

Several class options are available:

compact This package option is to be used when the text is required in a more compact form, occupying less vertical space. It proves convenient for works of fiction. The author employs it to render the [Code Ahead](#) book.

sparse Under this package option, every section commences on a new page.

*The sources are on GitHub at [yegor256/yb-book](#)

- manuscript** Whenever the format is not intended for Amazon printing but for some other purpose (the page size being A4), this option proves convenient. The author likewise employs it whenever the book is to be rendered for printing on paper for review purposes.
- authordraft** This option is appropriate when the document is a draft for reviewers (the page size being A4) and a watermark together with a compact form of the content is desired. The option is used in conjunction with the `\thereviewer{}` command, which may be redefined to embed the name of the reviewer within the watermark. This serves as a deterrent to theft of the book:

```
\documentclass[authordraft]{yb-book}
\renewcommand*\thereviewer{Walter Sobchak}
\begin{document}
Hello, world!
\end{document}
```

3 Meta Commands

A number of commands may be redefined within the preamble:

```
\documentclass{yb-book}
\newcommand*\thetitle{My New Book About OOP}
\newcommand*\theauthor{Yegor Bugayenko}
\newcommand*\thevolume{1}
\newcommand*\thedata{24 Feb 2022}
\newcommand*\theversion{1.4}
\newcommand*\thereviewer{Jeff Lebowski}
\begin{document}
... the content goes here ...
\end{document}
```

4 Printers

A number of printers are provided—commands that render substantial blocks of text in the expected format:

- `\ybPrintTitlePage` Prints the first page of a book. At minimum, `\thetitle` and `\theauthor` must be defined:

```
\documentclass{yb-book}
\renewcommand*\thetitle{My New Book}
\renewcommand*\theauthor{Yegor Bugayenko}
\begin{document}
\ybPrintTitlePage
.. the rest of the book goes here
\end{document}
```

- `\ybPrintTOC` Prints the table of contents.

- `\ybQuote` Prints a side quote:

```
\documentclass{yb-book}
```

```

\begin{document}
Hello, world!
\ybQuote{Never tell the truth to people who
are not worthy of it}{Mark Twain}{}
\end{document}

```

A warning is emitted to the log whenever the quotation falls very close to the top or the bottom of a page, since the underlying `wrapfig` environment behaves poorly in such positions.

`\ybPrintBibliography` Prints the list of bib references.

`\ybPrintIndex` Prints index with an optional name of the section (instead of “Index”):

```

\documentclass{yb-book}
\begin{document}
Hello, world!
\ybPrintIndex[Recommended Books]
\end{document}

```

5 Implementation

First, we parse package options:

```

1 \RequirePackage{pgfopts}
2 \pgfkeys{
3   /yb/.cd,
4   apa/.store in=\yb@apa,
5   authordraft/.store in=\yb@authordraft,
6   compact/.store in=\yb@compact,
7   manuscript/.store in=\yb@manuscript,
8   colored/.store in=\yb@colored,
9   sparse/.store in=\yb@sparse,
10 }
11 \ProcessPgfPackageOptions{/yb}

```

Then, depending on the options like `authordraft` and `manuscript`, we preset options of the class `book` and then load it:

```

12 \makeatletter
13 \ifdefined\yb@authordraft
14   \PassOptionsToClass{11pt}{book}
15   \PassOptionsToClass{oneside}{book}
16 \else
17   \ifdefined\yb@manuscript
18     \PassOptionsToClass{12pt}{book}
19     \PassOptionsToClass{oneside}{book}
20   \else
21     \PassOptionsToClass{11pt}{book}
22     \PassOptionsToClass{twoside}{book}
23   \fi
24 \fi
25 \makeatother
26 \LoadClass{book}

```

Then, we load `href-ul` to underline links correctly:

```

27 \RequirePackage{href-ul}

```

Then, we load [cleveref](#) for the `\cref` command:

```
28 \PassOptionsToPackage{capitalize}{cleveref}
29 \RequirePackage{amsmath}
30 \RequirePackage{cleveref}
31 \crefformat{section}{\S#2#1#3}
```

The class does not change the main font; the default Computer Modern Roman is used. Document authors are free to select a different font in their own preamble.

`geometry` Then, using `geometry`, we set up page layout:

```
32 \RequirePackage{geometry}
33 \geometry{
34   paperwidth=6in, paperheight=9in,
35   bindingoffset=0.25in,
36   left=0.75in, right=0.75in, top=0.75in, bottom=1.25in}
37 \makeatletter
38 \ifdefined\yb@authordraft
39   \geometry{a4paper, margin=1in, left=1.5in}
40 \else
41   \ifdefined\yb@manuscript
42     \geometry{a4paper, margin=1.2in}
43   \fi
44 \fi
45 \makeatother
```

Then, we load [anyfontsize](#) to enable all sizes of fonts:

```
46 \RequirePackage{anyfontsize}
```

Then, we load [tikz](#) for graphics:

```
47 \RequirePackage{tikz}
48 \usetikzlibrary{positioning}
49 \usetikzlibrary{shapes}
50 \usetikzlibrary{fit}
```

Then, we load [chngcntr](#) for something else:

```
51 \RequirePackage{chngcntr}
52 \counterwithout{footnote}{chapter}
```

Then, we load [handstroke](#) to enable `\hs` command to underline:

```
53 \PassOptionsToPackage{synonym=hs}{handstroke}
54 \RequirePackage{handstroke}
```

Then, we load [lastpage](#) to enable rendering of the last page number:

```
55 \RequirePackage{lastpage}
```

Then, we load [paralist](#) for inline enumeration:

```
56 \RequirePackage{paralist}
```

Then, we load [xcolor](#) for colors:

```
57 \RequirePackage{xcolor}
```

Then, we load [graphicx](#) to enable graphic files inclusion:

```
58 \RequirePackage{graphicx}
```

Then, we load `enumitem` for inline enumeration:

```
59 \PassOptionsToPackage{inline}{enumitem}
60 \RequirePackage{enumitem}
61 \setlist{nosep}
```

Then, we load `float` for floating figures:

```
62 \RequirePackage{float}
```

Then, we load `xfp` and `xifthen` for if-then-else:

```
63 \RequirePackage{xfp}
64 \RequirePackage{xifthen}
```

Then, we load `csquotes` for better rendering:

```
65 \PassOptionsToPackage{autostyle=try}{csquotes}
66 \RequirePackage{csquotes}
```

`\pagestyle` Then, we set the layout of a page to plain:

```
67 \pagestyle{plain}
```

`setspace` Then, using `setspace` package we set the spacing between lines in the text, depending on the package options:

```
68 \RequirePackage{setspace}
69 \setstretch{1.2}
70 \makeatletter
71 \ifdefined\yb@compact\setstretch{1.0}\fi
72 \ifdefined\yb@manuscript\setstretch{1.1}\fi
73 \ifdefined\yb@authordraft\setstretch{1.4}\fi
74 \makeatother
```

`biblatex` Then, we configure `biblatex` for citation management:

```
75 \PassOptionsToPackage{indexing=cite,
76 natbib=true,maxnames=2,minnames=1,doi=true,
77 url=false,isbn=false}{biblatex}
78 \makeatletter
79 \ifdefined\yb@apa
80 \PassOptionsToPackage{style=authoryear}{biblatex}
81 \else
82 \PassOptionsToPackage{style=numeric}{biblatex}
83 \fi
84 \makeatother
85 \RequirePackage{doi}
86 \RequirePackage{biblatex}
87 \DeclareCiteCommand{\citetitle}
88 {\boolfalse{citetracker}%
89 \boolfalse{pagetracker}%
90 \usebibmacro{prenote}}
91 {\ifciteindex
92 {\indexnames{labelname}}
93 {}%
94 \printfield[citetitle]{labeltitle}}
95 {\multicitedelim}
96 {\usebibmacro{postnote}}
97 \DeclareCiteCommand*{\citetitle}
98 {\boolfalse{citetracker}%
99 \boolfalse{pagetracker}%
```

```

100     \usebibmacro{prenote}}
101     {\ifcitereindex
102      {\indexnames{labelname}}
103      {}%
104      \printfield[citetitle]{title}}
105     {\multicitedelim}
106     {\usebibmacro{postnote}}

```

condensed Then, we define condensed environment for snippets:

```

107 \newenvironment{condensed}
108   {\beginngroup%
109    \lstset{columns=fixed, basewidth=0.45em}}
110   {\endgroup}

```

microtype Then, we include microtype for better rendering:

```

111 \makeatletter
112 \ifdefined\yb@authordraft
113   \PassOptionsToPackage{nopatch=footnote}{microtype}
114 \else
115   \PassOptionsToPackage{nopatch=footnote, protrusion=true}{microtype}
116 \fi
117 \makeatother
118 \RequirePackage{microtype}

```

\section Then, we redefine the \section command:

```

119 \makeatletter
120 \let\yb@oldsection\section
121 \def\yb@secstart{\ifdefined\yb@sparse\newpage\fi}
122 \ifdefined\yb@authordraft
123   \PassOptionsToPackage{medium}{titlesec}
124   \RequirePackage{titlesec}
125 \else
126   \PassOptionsToPackage{raggedright}{titlesec}
127   \RequirePackage{titlesec}
128   \titlespacing{\section}{0em}{2em}{1em}
129   \renewcommand\section{\yb@secstart\yb@oldsection}
130 \fi
131 \ifdefined\yb@compact
132   \renewcommand\section{\yb@secstart\vspace{2em}\yb@oldsection}
133 \fi
134 \makeatother

```

Then, we do small tweaking:

```

135 \makeatletter
136 \renewcommand\@makefnmark[1]{%
137   \raggedright%
138   \parindent=1em%
139   \noindent\hb@xt@1.8em{\hss\@makefnmark}\#1}
140 \makeatother

```

Then, if it's an authordraft, we put a watermark comment:

```

141 \makeatletter
142 \ifdefined\yb@authordraft
143   \PassOptionsToPackage{absolute}{textpos}

```

```

144 \RequirePackage{textpos}
145 \TPGrid{16}{16}
146 \RequirePackage{fancyhdr}
147 \pagestyle{fancy}
148 \renewcommand\headrulewidth{0em}
149 \renewcommand\footrulewidth{0em}
150 \setlength{\headheight}{3em}
151 \fancyhf{}
152 \fancyhead[L,C,L0,C0]{}
153 \fancyhead[R,R0]{}
154 \begin{textblock}[16][0.5,0.5](8,8)%
155 \tikz \node[minimum width=16\TPHorizModule] {%
156 \fontsize{64}{64}\selectfont\bfseries%
157 \rotatebox{45}{
158 \tikz \node
159 [fill=gray!6, font=\ttfamily\color{white}]
160 {it is a draft};%
161 }%
162 };%
163 \end{textblock}%
164 \begin{textblock}{4}(11.5,1)%
165 \tikz \node [color=gray, rotate=270,
166 font=\ttfamily\scriptsize, text width=24em] at (0,0) {%
167 Copyright \textcopyright{} \the\year{} by \theauthor{}.
168 All rights reserved. No part of the contents of
169 this book may be reproduced or transmitted in any
170 form or by any means without the written permission
171 of the publisher. This particular manuscript is
172 printed for \textbf{\thereviewer{}} and may be used only
173 for one-time review. The manuscript has to be destroyed
174 after the review.%
175 };
176 \end{textblock}
177 }
178 \fancyfoot[C,C0,C]{\small\ttfamily%
179 page \thepage{} of \pageref{LastPage}}
180 \fi
181 \makeatother

```

`\maketitle` Then, we redefine the `\maketitle` command:

```

182 \renewcommand\maketitle{
183 {\LARGE\textbf{\thetitle}}
184 \\[1em]
185 by \theauthor{}
186 \\[4em]
187 \ifx\thevolume\empty\else%
188 Volume \thevolume{}\\\
189 \fi
190 \ifx\thedata\empty\else%
191 Rendered on \thedata{}\\\
192 \fi
193 \ifx\theversion\empty\else%
194 Ver. \theversion{}
195 \fi

```

196 }

`\incolor` Then, we define the `\incolor` command:

```
197 \makeatletter
198 \newcommand\incolor[2]{%
199   \ifdefined\yb@colored\textcolor{#1}{#2}\else#2\fi}
200 \makeatother
```

`\ix` Then, we define the `\ix` command:

```
201 \newcommand\ix[2][]{%
202   \incolor{brown}{#2}%
203   \def\ixparam{#1}%
204   \ifx\ixparam\empty%
205     \index{#2}%
206   \else%
207     \index{#1}%
208   \fi}
```

`\emph` Then, we redefine the `\emph` command:

```
209 \renewcommand\emph[1]{\incolor{orange}{\textit{#1}}}
```

`\ybPrintTitlePage` Then, we define the `\ybPrintTitlePage` command:

```
210 \makeatletter
211 \newcommand\ybPrintTitlePage{
212   \ifdefined\yb@authordraft\else
213     \begin{titlepage}
214       \ttfamily
215       \vspace*{\fill}
216       \noindent
217       {\Huge\thetitle}
218       \\[1em]
219       by \theauthor{}
220       \\[4em]
221       \ifx\thevolume\empty\else%
222         Volume \thevolume{}\\\
223       \fi
224       \ifx\thedata\empty\else%
225         \thedata{}\\\
226       \fi
227       \ifx\theversion\empty\else%
228         \theversion{}
229       \fi
230       \vspace*{\fill}
231     \end{titlepage}
232   \fi
233 }
234 \makeatother
```

`\ybEpigraph` Then, we define the `\ybEpigraph` command to print the epigraph:

```
235 \newcommand\ybEpigraph[3]{
236   \cleardoublepage
237   \vspace*{\fill}
238   \begin{quote}
```



```

239 \begin{raggedleft}
240 ‘‘#1’’ \[1em]
241 {---} #2 \[
242 \citetitle{#3}\[
243 \citeyear{#3}\par
244 \end{raggedleft}
245 \end{quote}
246 \vspace*{\fill}}

```

`\ybPrintTOC` Then, we define the `\ybPrintTOC` command to print the table of contents:

```

247 \makeatletter
248 \newcommand\ybPrintTOC{%
249 \ifdefined\yb@authordraft\else%
250 \ifdefined\yb@compact\else\cleardoublepage\fi%
251 {\setstretch{0.7}\tableofcontents}%
252 \fi%
253 }
254 \makeatother

```

`\ybPrintIndex` Then, we configure the `imakeidx` package and define the `\ybPrintIndex` command:

```

255 \RequirePackage{imakeidx}
256 \renewbibmacro*{citeindex}{\indexnames{labelname}{}}
257 \makeindex
258 \indexsetup{othercode={\hyphenpenalty=10000}}
259 \makeatletter
260 \newcommand\ybPrintIndex[1][Index]{%
261 \ifdefined\yb@authordraft\else%
262 \ifdefined\yb@compact\else\cleardoublepage\fi%
263 {%
264 \setstretch{1.0}%
265 \small%
266 \addcontentsline{toc}{chapter}{#1}%
267 \printindex%
268 }%
269 \fi%
270 }
271 \makeatother

```

`\ybQuote` Then, with the help of `wrapfig` and `mdframed`, we define the `\ybQuote` command:

```

272 \RequirePackage{wrapfig}
273 \RequirePackage{mdframed}
274 \RequirePackage{changepage}
275 \strictpagecheck
276 \mdfdefinestyle{quoteodd}{backgroundcolor=black!0,
277 leftmargin=1em,rightmargin=0em,
278 innerleftmargin=1em,inerrightmargin=0em,
279 innertopmargin=0em,innerbottommargin=0em,
280 skipabove=0em,skipbelow=0em,
281 linewidth=.2em,
282 topline=false,bottomline=false,rightline=false}
283 \mdfdefinestyle{quoteeven}{backgroundcolor=black!0,
284 rightmargin=1em,leftmargin=0em,
285 innerrightmargin=1em,innerleftmargin=0em,
286 innertopmargin=0em,innerbottommargin=0em,

```

```

287 skipabove=0em,skipbelow=0em,
288 linewidth=.2em,
289 topline=false,bottomline=false,leftline=false}
290 \makeatletter
291 \newcommand\ybQuote[3]{%
292   \ifthenelse{\isempty{#3}}{}{
293     \ifx\hfuzz#2\hfuzz%
294       \index{#3}%
295     \else%
296       \index{#3, #2}%
297     \fi%
298   }%
299   \ifdim\pagetotal<4\baselineskip\relax%
300     \ClassWarning{yb-book}{ybQuote stays at the top of a page: \detokenize{#1}}%
301   \fi%
302   \ifdim\dimexpr\pagegoal-\pagetotal\relax<8\baselineskip\relax%
303     \ClassWarning{yb-book}{ybQuote stays at the bottom of a page: \detokenize{#1}}%
304   \fi%
305   \def\yb@body{%
306     \raggedright%
307     \ifx\hfuzz#3\hfuzz%
308       #1%
309     \else%
310       ‘‘#1’’\\raggedleft---#2 #3%
311     \fi%
312   }
313   \ifdefined\yb@authordraft%
314     \begin{wrapfigure}{r}{0.4\textwidth}%
315       \begin{mdframed}[style=quoteodd]%
316         \yb@body%
317       \end{mdframed}%
318     \end{wrapfigure}%
319   \else%
320     \begin{wrapfigure}{o}[2em]{0.4\textwidth}%
321       \sffamily\checkoddpag%
322       \ifoddpag%
323         \begin{mdframed}[style=quoteodd]\yb@body\end{mdframed}%
324       \else%
325         \begin{mdframed}[style=quoteeven]\yb@body\end{mdframed}%
326       \fi%
327       \vspace{-1em}
328     \end{wrapfigure}%
329   \fi%
330 }
331 \makeatother

```

\ybQuote Then, we define the \ybTweet command:

```

332 \makeatletter
333 \newcommand\ybTweet[1]{%
334   \ifdefined\yb@authordraft\else%
335     \ybQuote{#1}{}{}%
336   \fi%
337 }
338 \makeatother

```

Then, we use and configure footmisc as suggested [here](#):

```

339 \RequirePackage{perpage}
340 \PassOptionsToPackage{bottom,perpage,multiple}{footmisc}
341 \RequirePackage{footmisc}
342 \makeatletter
343 \let\yb@oldfootnote\footnote
344 \newcommand\yb@nexttoken\relax
345 \newcommand\yb@isfootnote{%
346   \ifx\footnote\yb@nexttoken\textsuperscript{,}\fi}
347 \renewcommand\footnote[1]{%
348   \yb@oldfootnote{#1}\futurelet\yb@nexttoken\yb@isfootnote}
349 \makeatother

```

\ybPrintBibliography Then, we define \ybPrintBibliography, to print a list of references:

```

350 \makeatletter
351 \newcommand\ybPrintBibliography[1][Bibliography]{%
352   \AtNextBibliography{\small}%
353   \raggedright%
354   \ifdefined\yb@manuscript%
355     \setlength\bibitemsep{0em}%
356     \newpage%
357     \begin{multicols}{2}%
358       {\setstretch{1.0}\printbibliography}%
359     \end{multicols}%
360   \else%
361     \setlength\bibitemsep{.2em}%
362     \@openrightfalse%
363     \printbibliography[heading=bibintoc,title={#1}]%
364     \ifdefined\yb@compact\@openrighttrue\fi%
365   \fi%
366 }
367 \makeatother

```

Then, a few layout configurations at the beginning of the document:

```

368 \makeatletter
369 \AtBeginDocument{%
370   \raggedbottom%
371   \ifdefined\yb@authordraft%
372     \raggedright%
373   \fi%
374   \setlength\topskip{0em}%
375   \setlength\parindent{0em}%
376   \setlength\fbboxsep{0em}%
377   \setlength\parskip{.5em}%
378   \exhyphenpenalty=10000% to avoid line breaks before and after an em dash
379   \widowpenalty=10000% to have fewer widows
380   \clubpenalty=10000% to have fewer orphans
381   \interfootnotelinepenalty=10000% to format footnotes better
382   \hfuzz=3pt %
383   \tolerance=1000 %
384   \emergencystretch=1em %
385   \hbadness=2000 %
386 }
387 \makeatother

```

Finally, a few meta commands with default values:

```
388 \newcommand*\thetitle{\textbackslash{}thetitle}
389 \let\thevolume\empty
390 \let\thedate\empty
391 \newcommand*\theversion{\textbackslash{}theversion}
392 \newcommand*\theauthor{\textbackslash{}theauthor}
393 \newcommand*\thereviewer{\textbackslash{}thereviewer}
394
395 \endinput
```

Change History

v0.1.0		v0.6.0	
General: Initial version	3	General: The apa package option added, to enable APA citation style.	3
v0.11.0		v0.6.2	
\ybQuote: The \ybTweet command added.	10	\ybPrintBibliography: The \ybPrintBibliography command has an optional argument, which is the title of the chapter.	11
v0.2.0		v0.6.6	
General: Started using l3build . . .	3	General: Penalties for widows and clubs specified.	11
v0.3.0		v0.7.0	
General: The pgfopts package is now used to parse package options.	3	General: Added cleveref package for the \bcref command.	4
v0.4.0		The colored package option added, to enable colors.	3
authordraft: The package option draft renamed to authordraft	2	v0.8.1	
v0.5.0		General: Removed the CMU Concrete font setup; the class no longer changes the main font and works under any engine. . .	4
General: The sparse package option added, to place every section on a new page.	3		
v0.5.1			
General: Added the usage of inputenc in order to ensure UTF-8 encoding for the sources.	4		

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	<code>\exhyphenpenalty</code> .. 378	<code>\ixparam</code> 203, 204
<code>\@makefnmark</code> 139	F	L
<code>\@makefntext</code> 136	<code>\fancyfoot</code> 178	<code>\LARGE</code> 183
<code>\@openrightfalse</code> .. 362	<code>\fancyhead</code> 152, 153	<code>\LoadClass</code> 26
<code>\@openrighttrue</code> ... 364	<code>\fancyhf</code> 151	<code>\lstset</code> 109
<code>\@</code> 184, 186, 188, 191, 218, 220, 222, 225, 240, 241, 242, 310	<code>\fboxsep</code> 376	M
A	<code>\fill</code> . 215, 230, 237, 246	<code>\makeatletter</code>
<code>\addcontentsline</code> .. 266	<code>\fontsize</code> 156	 12, 37, 70, 78, 111, 119, 135, 141, 197, 210, 247, 259, 290, 332, 342, 350, 368
<code>Amazon</code> 1	<code>\footnote</code> . 343, 346, 347	<code>\makeatother</code>
<code>\AtBeginDocument</code> .. 369	<code>\footrulewidth</code> 149	 25, 45, 74, 84, 117, 134, 140, 181, 200, 234, 254, 271, 331, 338, 349, 367, 387
<code>\AtNextBibliography</code> 352	<code>\futurelet</code> 348	<code>\makeindex</code> 257
<code>\authordraft</code> <u>1</u>	G	<code>\maketitle</code> <u>182</u>
B	<code>\geometry</code> <u>32</u> , 33, 39, 42	<code>\manuscript</code> <u>1</u>
<code>\baselineskip</code> . 299, 302	H	<code>\mdfdefinestyle</code> 276, 283
<code>\bfseries</code> 156	<code>\hb@xt@</code> 139	<code>\microtype</code> 111
<code>\bibitemsep</code> ... 355, 361	<code>\hbadness</code> 385	<code>\multicitedelim</code> 95, 105
<code>\biblatex</code> <u>75</u>	<code>\headheight</code> 150	N
<code>\boolfalse</code> 88, 89, 98, 99	<code>\headrulewidth</code> 148	<code>\newpage</code> 121, 356
C	<code>\hfuzz</code> 293, 307, 382	<code>\node</code> 155, 158, 165
<code>\checkoddpage</code> 321	<code>\hss</code> 139	<code>\noindent</code> 139, 216
<code>\citetitle</code> .. 87, 97, 242	<code>\Huge</code> 217	P
<code>\citeyear</code> 243	<code>\hyphenpenalty</code> 258	<code>\pagegoal</code> 302
<code>\ClassWarning</code> . 300, 303	I	<code>\pageref</code> 179
<code>\cleardoublepage</code> 236, 250, 262	<code>\ifciteindex</code> ... 91, 101	<code>\pagestyle</code> <u>67</u> , 147
<code>\clubpenalty</code> 380	<code>\ifdefined</code> ... 13, 17, 38, 41, 71, 72, 73, 79, 112, 121, 122, 131, 142, 199, 212, 249, 250, 261, 262, 313, 334, 354, 364, 371	<code>\pagetotal</code> 299, 302
<code>\color</code> 159	<code>\ifdim</code> 299, 302	<code>\par</code> 243
<code>\compact</code> <u>1</u>	<code>\ifoddpage</code> 322	<code>\parindent</code> 138, 375
<code>\condensed</code> <u>107</u>	<code>\ifthenelse</code> 292	<code>\parskip</code> 377
<code>\counterwithout</code> ... 52	<code>\ifx</code> ... 187, 190, 193, 204, 221, 224, 227, 293, 307, 346	<code>\PassOptionsToClass</code> 14, 15, 18, 19, 21, 22
<code>\crefformat</code> 31	<code>\incolor</code> .. 197, 202, 209	<code>\PassOptionsToPackage</code> 28, 53, 59, 65, 75, 80, 82, 113, 115, 123, 126, 143, 340
D	<code>\index</code> 205, 207, 294, 296	
<code>\DeclareCiteCommand</code> 87, 97	<code>\indexnames</code> 92, 102, 256	
<code>\detokenize</code> ... 300, 303	<code>\indexsetup</code> 258	
<code>\dimexpr</code> 302	<code>\interfootnotelinepenalty</code> 381	
E	<code>\ix</code> <u>201</u>	
<code>\emergencystretch</code> .. 384		
<code>\emph</code> <u>209</u>		
<code>\endinput</code> 395		

<code>\pgfkeys</code> 2	<code>\setstretch</code> . . 69, 71,	<code>\usetikzlibrary</code> . . .
<code>\printbibliography</code> .	72, 73, 251, 264, 358	 48, 49, 50
. 358, 363	<code>\sffamily</code> 321	
<code>\printfield</code> 94, 104	<code>\small</code> 178, 265, 352	V
<code>\printindex</code> 267	<code>\sparse</code> 1	<code>\vspace</code> . . . 132, 215,
<code>\ProcessPgfPackageOptions</code>	<code>\strictpagecheck</code> . . 275	230, 237, 246, 327
. 11		
	T	W
R	<code>\tableofcontents</code> . . 251	<code>\widowpenalty</code> 379
<code>\raggedbottom</code> 370	<code>\textbackslash</code>	
<code>\raggedleft</code> 310	. . 388, 391, 392, 393	Y
<code>\raggedright</code>	<code>\textbf</code> 172, 183	<code>\yb@apa</code> 4, 79
. . 137, 306, 353, 372	<code>\textcolor</code> 199	<code>\yb@authordraft</code> 5, 13,
<code>\relax</code> 299, 302, 344	<code>\textcopyright</code> 167	38, 73, 112, 122,
<code>\renewbibmacro</code> 256	<code>\textit</code> 209	142, 212, 249,
<code>\renewcommand</code> . . 129,	<code>\textsuperscript</code> . . 346	261, 313, 334, 371
132, 136, 148,	<code>\textwidth</code> 314, 320	<code>\yb@body</code> 305, 316, 323, 325
149, 182, 209, 347	<code>\the</code> 167	<code>\yb@colored</code> 8, 199
<code>\RequirePackage</code> . . .	<code>\theauthor</code>	<code>\yb@compact</code> . . . 6, 71,
. 1, 27, 29,	. . 167, 185, 219, 392	131, 250, 262, 364
30, 32, 46, 47, 51,	<code>\thedata</code> 190,	<code>\yb@isfootnote</code> 345, 348
54, 55, 56, 57, 58,	191, 224, 225, 390	<code>\yb@manuscript</code>
60, 62, 63, 64, 66,	<code>\thepage</code> 179	. . 7, 17, 41, 72, 354
68, 85, 86, 118,	<code>\thereviewer</code> . . 172, 393	<code>\yb@nexttoken</code>
124, 127, 144,	<code>\thetitle</code> . 183, 217, 388	 344, 346, 348
146, 255, 272,	<code>\theversion</code> 193,	<code>\yb@oldfootnote</code> 343, 348
273, 274, 339, 341	194, 227, 228, 391	<code>\yb@oldsection</code>
<code>\rotatebox</code> 157	<code>\thevolume</code> 187,	 120, 129, 132
	188, 221, 222, 389	<code>\yb@secstart</code> 121, 129, 132
S	<code>\tikz</code> 155, 158, 165	<code>\yb@sparse</code> 9, 121
<code>\S</code> 31	<code>\titlespacing</code> 128	<code>\yb@Epigraph</code> 235
<code>\scriptsize</code> 166	<code>\tolerance</code> 383	<code>\ybPrintBibliography</code>
<code>\section</code> 119	<code>\topskip</code> 374	 1, 350
<code>\selectfont</code> 156	<code>\TPGrid</code> 145	<code>\ybPrintIndex</code> . . . 1, 255
<code>\setlength</code>	<code>\TPHorizModule</code> 155	<code>\ybPrintTitlePage</code> 1, 210
. . 150, 355, 361,	<code>\ttfamily</code>	<code>\ybPrintTOC</code> 1, 247
374, 375, 376, 377	. . 159, 166, 178, 214	<code>\ybQuote</code> . . . 1, 272, 332
<code>\setlist</code> 61	U	<code>\ybTweet</code> 333
<code>\setspace</code> 68	<code>\usebibmacro</code>	<code>\year</code> 167
	. . 90, 96, 100, 106	