

The latex-lab-testphase-new-or-2 code

Frank Mittelbach, L^AT_EX Project

v0.86d 2026-01-16

Abstract

This code implements changes to the output routine intended to be moved in the L^AT_EX kernel at some point in the future.

1 Introduction

2 The Implementation

1 `<*package>`

2.1 File declaration

```
2 \ProvidesPackage{latex-lab-testphase-new-or-2}
3     [\ltxlabneworIIdate\space v\ltxlabneworIIversion\space
4     Changes to the output routine]
```

2.2 \@makecol reimplementaion

`footnote-floats` (*plug*) If `\DocumentMetadata` is used we use `footnotes-floats` as the default. In 2e compatibility mode this should be changed to `footnotes-floats-legacy`.

```
5 \AssignSocketPlug {build/column/outputbox}{footnotes-floats}
```

`\@makecol@handlesplitfootnotes` This is only an early draft and doesn't do much. Contains incomplete preparation for tagging commented out.
`\@makecol@splitfootnotemessagehook`

TODO: Interfaces and code will change in the future

```
6 \def\@makecol@handlesplitfootnotes {%
7 % \ifx\splitfootnote@continuation\@empty \else
8 % \setbox\footins\vbox{\splitfootnote@continuation\unvbox\footins}%
9 % \global\let\splitfootnote@continuation\@empty
10 % \fi
11 \ifnum\insertpenalties>\z@
12 \@makecol@splitfootnotemessagehook
13 % \setbox\footins\vbox{\unvbox\footins --- END at split}%
14 % \gdef\splitfootnote@continuation {--- START after split}%
15 \fi
16 }
17 %\def\splitfootnote@continuation{}
```

This could issue warning if split footnotes are encountered.

```
18 \let \@makecol@splitfootnotemessagehook \empty
(End of definition for \@makecol@handlesplitfootnotes and \@makecol@splitfootnotemessagehook.)
```

2.3 \@outputpage reimplementation

We still have to deal with various plug setting for tagging: This needs documentation and moving.

default (*plug*)

```
19 \ExplSyntaxOn
    TODO: where should these plug declarations go? tagpdf?
20 \NewTaggingSocketPlug{build/page/header}{default}
21 {
22     \__tag_hook_kernel_before_head:
23     #2
24     \__tag_hook_kernel_after_head:
25 }
26 \AssignTaggingSocketPlug{build/page/header}{default}
```

default (*plug*)

```
27 \NewTaggingSocketPlug{build/page/footer}{default}
28 {
29     \__tag_hook_kernel_before_foot:
30     #2
31     \__tag_hook_kernel_after_foot:
32 }
33 \AssignTaggingSocketPlug{build/page/footer}{default}
```

default (*plug*)

```
34 \NewTaggingSocketPlug{build/column/outputbox}{default}
35 {
36     \__tag_check_typeout_v:n { ==>~In~\token_to_str:N \@makecol
37                             \c_space_tl\the\c@page }
38     \tag_mc_add_missing_to_stream:Nn \@outputbox {main}
39 }
```

default (*plug*)

```
40 \NewTaggingSocketPlug{build/column/footins}{default}
41 { \tag_mc_add_missing_to_stream:Nn \footins {footnote} }
```

The two sockets do nothing (default noop) if we are in lua mode. If not they get the default assigned

```
42 \sys_if_engine luatex:F
43 {
44     \AssignTaggingSocketPlug{build/column/outputbox}{default}
45     \AssignTaggingSocketPlug{build/column/footins}{default}
46 }
47 \ExplSyntaxOff
```

3 Replacement for the footmisc package

The replacement for footmisc. If the new code is used, we must replace the package if it is loaded by the user:

```
48 \declare@file@substitution{footmisc.sty}{latex-lab-footmisc.ltx}
```

This can be removed the moment the remaining hooks and sockets have been integrated into footmisc, which will probably not happen before the 2025/11 release.

4 Temp stuff that is related but should go to the kernel

This is the code from latex-lab-footnotes.dtx.

```
49 \input{latex-lab-footnotes.ltx}
```

```
50 \</package>
```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

A		L	
\AssignSocketPlug	5	\input	49
\AssignTaggingSocketPlug	26, 33, 44, 45	\insertpenalties	11
D		L	
\def	6, 17	\let	9, 18
default (plug)	2, 19, 27, 34, 40	\ltlabneworIIdate	3
\DocumentMetadata	1	\ltlabneworIIversion	3
E		N	
\else	7	\NewTaggingSocketPlug	20, 27, 34, 40
\ExplSyntaxOff	47	noop (plug)	2
\ExplSyntaxOn	19	P	
F		Plugs:	
\fi	10, 15	default	2, 19, 27, 34, 40
\footins	8, 13, 41	footnote-floats	5
footnote-floats (plug)	5	footnotes-floats	1
footnotes-floats (plug)	1	footnotes-floats-legacy	1
footnotes-floats-legacy (plug)	1	noop	2
G		\ProvidesPackage	2
\gdef	14	S	
\global	9	\setbox	8, 13
I		\space	3
\ifnum	11	sys commands:	
\ifx	7	\sys_if_engine luatex:TF	42

T		\@outputpage 2	
tag commands:		\c@page 37	
\tag_mc_add_missing_to_stream:Nn		\declare@file@substitution 48	
..... 38, 41		\splitfootnote@continuation	
tag internal commands:	 7, 8, 9, 14, 17	
__tag_check_typeout_v:n 36		\z@ 11	
__tag_hook_kernel_after_foot: .. 31		\the 37	
__tag_hook_kernel_after_head: .. 24		tl commands:	
__tag_hook_kernel_before_foot: . 29		\c_space_tl 37	
__tag_hook_kernel_before_head: . 22		token commands:	
T _E X and L ^A T _E X 2 _ε commands:		\token_to_str:N 36	
\@empty 7, 9, 18			
\@makecol 1, 36			
\@makecol@handlesplitfootnotes ... 6			
\@makecol@splitfootnotemessagehook			
..... 6			
\@outputbox 38			